



Screedex™

Base Coat – Concrete

DESCRIPTION

Screedex™ is a Screed Concrete laid in a range of thickness, and its purpose is to bring the installation surface of flooring to the design height & level.

RECOMMENDED USES

1. Base Coat for installing specified flooring.
2. Floating finish for rigid insulation material.
3. Bond coat between under laying, water pipes & specified flooring.
4. Can be set as guide for straight edges for bringing concrete surface to desired slopes/elevations.
5. Can be used as back filling element.

FEATURES & BENEFITS

1. As it is pumpable concrete, it eradicates hassles of manual transportation of material to prepare base coat for flooring.
2. It can be laid on large area which will benefit in time and cost saving.
3. With adherent feature of pumping & negligible strength, it becomes very easy to chisel for conduiting.
4. It is very compact and homogeneous throughout the thickness of application.
5. Its low cementations nature assists in reduction in heat of hydration, which reduces thermal cracking.
6. As it's a factory mixed product and delivered to site, which offers additional quality assurance.
7. Can be applied in thickness as low as 35mm.

CURING

Like all cementitious products, Screedex must be protected against rapid drying due to temp and /or strong wind. To avoid shrinkage cracks, it is advisable to sprinkle water immediately upon initial setting. If the area is exposed to sunlight then tightly cover it with plastic membrane in such a way so that water evaporation loss is minimum.